



## TYRESÖSTÖTTAN – LCF<sub>e</sub> Galvanized boat stand

Demountable hot-dip galvanized steel stand with integrated quick couplers for safety chain – easy, worry-free installation and maintenance with best operating reliability.



Delivered disassembled in box. Mitered end.

Type	Max load (kg/lbs)	Height (mm/inch)		Weight (approx. kg/lbs)	Gross weight (approx. kg/lbs)	Box size LxWxH (mm/inch)
		~ min	~ max			
LCF <sub>e</sub> 80	1500/3306	800/32	1250/49	16/35	17/37	840x240x140/33x9,5x5,5
LCF <sub>e</sub> 110		1100/44	1550/61	19/41	20/44	1100x240x140/43,3x9,5x5,5
LCF <sub>e</sub> 130		1300/52	1750/68	21/46	22/48	1300x240x140/51,2x9,5x5,5
LCF <sub>e</sub> 150		1500/59	1950/76	23/50	25/55	1510x240x140/59,5x9,5x5,5
LCF <sub>e</sub> 170		1700/67	2150/84	25/55	27/59	1710x240x140/67,3x9,5x5,5
LCF <sub>e</sub> 190		1900/75	2350/92	28/61	30/66	2110x240x140/83x9,5x5,5
Safety Chain	Length ~ 3,05 m/10 foot		1,5/3,3	1,6/3,5	140x140x45/5,5x5,5x1,8	

Profiled hull pad of quality rubber – best friction and protection.

Hot-dip galvanized, trapezoidal threaded rod and winged nut – fast and easy adjustment.

Hot-dip galvanized steel top plate (stainless steel screw/locking nut) with integrated quick couplers for safety chain – easy, worry-free installation and maintenance.



## TYRESÖSTÖTTAN – LCM<sub>e</sub> Galvanized boat stand

Demountable hot-dip galvanized steel stand with integrated quick couplers for safety chain – easy, worry-free installation and maintenance with best operating reliability.



Delivered disassembled in box. Mitered end.

Type	Max load (kg/lbs)	Height (mm/inch)		Weight (approx. kg/lbs)	Gross weight (approx. kg/lbs)	Box size LxWxH (mm/inch)
		~ min	~ max			
LCM <sub>e</sub> 500	2750/6062	500/20	800/31	11/24	12/26	520x390x160/20,5x15,4x6,3
LCM <sub>e</sub> 600		600/24	900/35	12/26	13/28	630x390x160/24,8x15,4x6,3
LCM <sub>e</sub> 750		750/30	1050/41	15/33	17/37	780x480x160/30,7x18,9x6,3
LCM <sub>e</sub> 900		900/36	1200/47	16/35	18/39	930x480x160/36,6x18,9x6,3
Safety Chain	Length ~ 3,05 m/10 foot		1,5/3,3	1,6/3,5	140x140x45/5,5x5,5x1,8	



Profiled hull pad of quality rubber – best friction and protection.

Hot-dip galvanized, trapezoidal threaded rod and winged nut – fast and easy adjustment.

Hot-dip galvanized steel top plate (stainless steel screw/locking nut) with integrated quick couplers for safety chain – easy, worry-free installation and maintenance.



**Safety Chain must always be used between the pair of stands**



**Maskinfabriken G-C A.B.**

Thulevägen 18, S-135 55 TYRESÖ  
 Phone. +46 8 712 50 90  
 info@gcboathandling.com  
 info@tyresovaggan.com  
 www.gcboathandling.com  
 www.tyresovaggan.com